

**CMT-663**

**RECESSED LONG WOOD GRAIN PANEL STEEL INSULATED DOOR**

**SERIES FEATURES**

- 1 3/8" (34.9mm) - Thick CFC-Free Polyurethane
- 13.45 Calculated R-Value
- .074 Calculated U-Value
- 26-Gauge Galvanized Steel
- Full Thermal Break
- Available with Wind Load
- 21 Color Options
- Industry Leading Warranty
- 10-Year Rust & Delamination
- 6-Year Hardware
- 3-Year Spring

**Cross Section**



**1 3/8" (34.9mm)  
Thick Sections**

**AVAILABLE COLORS**




Colors are not exact due to the differences in monitor and printer calibrations. For accurate color samples, contact Haas Door for a metal color selector. Trinar® colors carry a 35 year paint warranty.

**MODEL FEATURES**

- Extruded End Cap
- Recessed Long Panel wood grain embossment on outside, V-Groove pattern wood grain embossment inside
- Tongue and groove section joint

**Exterior View**



**Interior View**



**600 SERIES LINKS**

*Click links for info.*

**HOMEPAGE**

**BIM**

**BROCHURE**

**SPECS**

**GALLERY**

**SPECWIZARD**

**CAD**

**CATALOG**

Rev. 2.1 – October 2017